

2901

CVe-Monitor
Cve Monitor
Monitor Cve

Cve pametni števec
Cve monitor
Cve monitor



2901.CVe-M



Cve MONITOR

Progressive's Cve Monitor incorporates a 7-digit display with a button to move through the different data modes reporting on the tool's performance. Installation can be at parting line or below, and accessories including blocks and cables are available.

- Maximum temperature is 190°F (90°C)
- For heat protection, refer to the Insulators available here.



2901.CVe-M

2901.CVe-O



Cve MONITOR

Progressive's Cve Monitor incorporates a 7-digit display with a button to move through the different data modes reporting on the tool's performance. Installation can be at parting line or below, and accessories including blocks and cables are available.

- Maximum temperature is 190°F (90°C)
- For heat protection, refer to the Insulators available here.



2901.CVe-O

2901.CV

S = Standard

H = High temperature

Counter View



- Maximum operating temperatures:
- Standard CounterView: 250°F (120°C)



2901.CV-S

Counter View



- Maximum operating temperatures:
- High Temp CounterView: 375°F (190°C)



2901.CV-H

COUNTERVIEW: S-SERIES

Progressive's CounterView monitors mold cycle counts for the life of the tool. A-side and B-side versions are available and external mounting or extensions for installation away from the parting line are also offered. All CounterViews include both inch and metric screws.